



TECHNICAL FEATURE


FEATURES

- Space Qualified
- 1.0 2.7 GHz
- 2 Way

Model Number	Frequency Range GHz	lsolation dB Min.	Insertion Loss, dB Max.	Phase Balance Max.	Amplitude Balance dB Max.	VSWR Max.		CW Input, W, Load VSWR out	Weight
						In	Out	1.2:1	Max.
PDG-02B-1850 SQ	1.0 - 2.7	15	1	±2°	±0.2	1.6:1	1.6:1	1	2.8 g.

TECHNICAL DESCRIPTION / APPLICATION

The PDG-02B-1850 SQ In-Phase Power Divider covers 1.0 - 2.7 GHz. with a special lumped element design to reduce size, while maintaining high performance. This unit has been designed, manufactured, and qualified per Merrimac document CENG-0001, "Standard Design Requirements for Space Qualified Devices."



Microwave Solutions

Merrimac Industries 41 Fairfield Place, West Caldwell, NJ 07006

+ 1 973-575-1300, 191309 info@craneae.com www.craneae.com Page 1 of 1 PDG-02B-1850 SQ Rev.-, 09/13/2024

DS_Power Divider_PDG-02B-1850 SQ_09132024.indd. This revision supersedes all previous releases. All technical information is believed to be accurate, but no responsibility is assumed for errors. We reserve the right to make changes in products or specifications without notice. Copyright © 2024 Crane Electronics, Inc. All rights reserved.